

Fuseal 25/50™

PVDF Corrosive Waste Piping System

// Pipe, Fittings, Accessories
// Electrofusion





Fuseal 25/50™

PVDF Corrosive Waste Piping System

Overview

Fuseal 25/50™ PVDF piping system is an engineered solution for return air plenum piping; conveyance of aggressive chemicals at elevated temperatures; and waste streams with fats, oils, and grease due to its smooth inner walls and ability to flush with very hot water.

PVDF provides a very broad range of chemical resistance and thermal stability and is certified by UL 723/ASME E-84 to meet low flame spread and smoke density requirements.

Fuseal 25/50 is joined using state-of-the-art electrofusion.

The Fuseal 25/50 product line carries adapters for joining the PVDF system to our Fuseal PP system or other materials, as necessary.



Fuseal 25/50™ benefits

- State-of-the-art fusion technology from the company that introduced electrofusion
- Superior chemical resistance. Recommended for aggressive chemicals
- Abrasion resistance
- Excellent UV resistance
- Light weight for ease of installation
- High impact resistance
- A flame spread of less than 25 and a smoke development of less than 50 when tested to UL 723/ASTM E-84. Certified by UL
- Technical design and field support from distributor and GF Piping Systems personnel
- On-site training and certification (test) for all installers on product assembly and proper use of electrofusion equipment
- Performance at elevated temperatures up to 284°F
- Installation time 30% faster than competitive slip joint method
- 2.5× safety factor with a permanent electrofused joint
- Greater pipe wall integrity by eliminating any grooving

Code requirements

In recent years, federal, state, and local regulations have mandated the reduction of sources of fire and smoke in buildings. Return air plenums are of particular concern in that they can allow the rapid development of smoke and flame throughout a building. Many architects and engineers utilize the space above drop ceilings as return air plenums, and piping systems in these plenums may be required to meet stringent flame spread and smoke density standards.

Flame-retardant PVDF piping system

Fuseal 25/50 PVDF system uses Polyvinylidene Fluoride (PVDF) material, which is considered non-combustible as defined in UL 723. This material provides a very broad range of chemical resistance as well as a low flame spread and smoke density. Utilizing the ASTM E-84 testing, PVDF is the only plastic piping material currently available that can meet the stringent requirements of many current building codes.

PVDF is resistant to most inorganic acids as well as to aliphatic and aromatic hydrocarbons, organic acids, alcohols and halogenated solvents. PVDF also has some resistance to wet and dry halogens (with the exception of atomic fluoride). PVDF is not resistant to alkaline amines, alkalis and alkaline metals. Strong polarized solvents, such as ketones and organic acid esters, swell PVDF slightly.

Applications

- Corrosive waste drainage for return air plenums
- Corrosive waste drainage at elevated temperatures
- Industrial and special waste
- Waste streams with fats, oils, and grease, and elevated temperature water flushing

Industries

- Life Sciences
- Chemical Process Industry
- Food and Beverage

Product range

Fittings	Connection	Size	Material
Molded and fabricated	• Socket (electrofusion) • Union (MJ) transition adapters (PVDF/PP)	1½"–6"	PVDF
Pipe	Connection	Size	Material
Schedule 40		1½"–6"	PVDF

Pressure rating

- 30 foot (15 PSI) maximum head pressure test for DWV applications
- Up to 50 PSI for pressure waste applications (subject to manufacturers review of design)

Operating temperature

- -4°F–284°F (-20°C–140°C)

Joining technology

- Electrofusion

Meets the following standards

- ASTM D1599
- ASTM D2122
- ASTM D3222
- ASTM D3311
- ASTM D4101
- ASTM E84
- ASTM F1290
- ASTM F1673
- UL 723
- NFPA 255

Accessories

GF Piping Systems has engineered accessories to provide a complete solution. From non-standard items such as custom spool pieces to special custom fabrications, we will work with you to assist in supplying a complete system.

- Neutralization tanks
- Sinks
- Traps
- Monitoring equipment and systems
- Fuseal Squared® PP double containment piping
- Contain-It™ PVC secondary containment piping
- Custom spool pieces
- Custom fabrication

Electrofusion process

Electrofusion joining method is defined as the joining process where two plastic parts are fused utilizing electrical heat resistance to form a permanent joint.

A plastic-coated copper wire is wound into a coil and is then inserted into a fitting socket.

The pipe is then inserted into the fitting socket and an electric current is applied to the coil, producing heat that generates sufficient temperatures to melt the surrounding plastic and create a "melt zone."

Fusion occurs when the joint cools below the melt temperature of the plastic material, leaving a permanent joint that is proven to be as strong as, if not stronger than, the individual components.

Electro Plus® fusion machine

- Intuitive user interface
- Multiple joint capability for speedy installations
- Integral carrying case for ease of transportation
- Network and generator compatible for simple operation
- Self-diagnostic system takes the guesswork out of error detection
- Fusion cycle times automatically adjusted based on air temperature (ATC)
- One-button repeat fusion cycle for same size joints
- Use to install Fuseal® PP, Fuseal 25/50™, and Fuseal Squared® special waste piping systems as well as PPro-Seal™ natural PP process water piping systems

Electro Plus fusion machine



Worldwide at home

Our sales companies and representatives
ensure local customer support in over 100 countries

www.gfps.com

Argentina / Southern South America

Georg Fischer Central Plastics
Sudamérica S.R.L.
Buenos Aires, Argentina
Phone +54 11 4512 02 90
gfccentral.ps.ar@georgfischer.com
www.gfps.com/ar

Australia

Georg Fischer Pty Ltd
Riverwood NSW 2210 Australia
Phone +61 (0) 2 9502 8000
australia.ps@georgfischer.com
www.gfps.com/au

Austria

Georg Fischer
Rohrleitungssysteme GmbH
3130 Herzogenburg
Phone +43 (0) 2782 856 43-0
austria.ps@georgfischer.com
www.gfps.com/at

Belgium / Luxembourg

Georg Fischer NV/SA
1070 Bruxelles/Brüssel
Phone +32 (0) 2 556 40 20
be.ps@georgfischer.com
www.gfps.com/be

Brazil

Georg Fischer Sist. de Tub. Ltda.
04795-100 São Paulo
Phone +55 (0) 11 5525 1311
br.ps@georgfischer.com
www.gfps.com/br

Canada

Georg Fischer Piping Systems Ltd
Mississauga, ON L5T 2B2
Phone +1 (905) 670 8005
Fax +1 (905) 670 8513
ca.ps@georgfischer.com
www.gfps.com/ca

China

Georg Fischer Piping Systems Ltd
Shanghai 201319
Phone +86 21 3899 3899
china.ps@georgfischer.com
www.gfps.com/cn

Denmark / Iceland

Georg Fischer A/S
2630 Taastrup
Phone +45 (0) 70 22 19 75
info.dk.ps@georgfischer.com
www.gfps.com/dk

Finland

Georg Fischer AB
01510 VANTAA
Phone +358 (0) 9 586 58 25
Fax +358 (0) 9 586 58 29
info.fi.ps@georgfischer.com
www.gfps.com/fi

France

Georg Fischer SAS
95932 Roissy Charles de Gaulle Cedex
Phone +33 (0) 1 41 84 68 84
fr.ps@georgfischer.com
www.gfps.com/fr

Germany

Georg Fischer GmbH
73095 Albershausen
Phone +49 (0) 7161 302-0
info.de.ps@georgfischer.com
www.gfps.com/de

India

Georg Fischer Piping Systems Ltd
400 076 Mumbai
Phone +91 224007 2001
branchoffice@georgfischer.com
www.gfps.com/in

Indonesia

Georg Fischer Pte Ltd –
Representative Office
Phone +62 21 2900 8564
Fax +62 21 2900 8566
sgp.ps@georgfischer.com
www.gfps.com/sg

Italy

Georg Fischer S.p.A.
20063 Cernusco S/N (MI)
Phone +39 02 921 861
it.ps@georgfischer.com
www.gfps.com/it

Japan

Georg Fischer Ltd
556-0011 Osaka,
Phone +81 (0) 6 6635 2691
jp.ps@georgfischer.com
www.gfps.com/jp

Korea

GF Piping Systems
Georg Fischer Korea Co., Ltd.
Unit 2501, U-Tower
120 HeungdeokJungang-ro (Yeongdeok-dong)
Giheung-gu, Yongin-si, Gyeonggi-do, Korea
Phone: +82 31 8017 1450
Fax: +82 31 217 1454
kor.ps@georgfischer.com
www.gfps.com/kr

Malaysia

Georg Fischer (M) Sdn. Bhd.
40460 Shah Alam, Selangor Darul Ehsan
Phone +60 (0) 3 5122 5585
Fax +603 5122 5575
my.ps@georgfischer.com
www.gfps.com/my

Mexico / Northern Latin America

Georg Fischer S.A. de C.V.
Apodaca, Nuevo Leon
CP66636 Mexico
Phone +52 (81) 1340 8586
Fax +52 (81) 1522 8906
mx.ps@georgfischer.com
www.gfps.com/mx

Middle East

Georg Fischer
Piping Systems (Switzerland) Ltd
Dubai, United Arab Emirates
Phone +971 4 289 49 60
gcc.ps@georgfischer.com
www.gfps.com/int

Netherlands

Georg Fischer N.V.
8161 PA Epe
Phone +31 (0) 578 678 222
nl.ps@georgfischer.com
www.gfps.com/nl

Norway

Georg Fischer AS
1351 Rud
Phone +47 67 18 29 00
no.ps@georgfischer.com
www.gfps.com/no

Philippines

Georg Fischer Pte Ltd
Representative Office
Phone +632 571 2365
Fax +632 571 2368
sgp.ps@georgfischer.com
www.gfps.com/sg

Poland

Georg Fischer Sp. z o.o.
05-090 Sekocin Nowy
Phone +48 (0) 22 31 31 0 50
poland.ps@georgfischer.com
www.gfps.com/pl

Romania

Georg Fischer
Piping Systems (Switzerland) Ltd
020257 Bucharest - Sector 2
Phone +40 (0) 21 230 53 80
ro.ps@georgfischer.com
www.gfps.com/int

Russia

Georg Fischer
Piping Systems (Switzerland) Ltd
Moscow 125047
Phone +7 495 258 60 80
ru.ps@georgfischer.com
www.gfps.com/ru

Singapore

Georg Fischer Pte Ltd
11 Tampines Street 92, #04-01/07
528 872 Singapore
Phone +65 6747 0611
Fax +65 6747 0577
sgp.ps@georgfischer.com
www.gfps.com/sg

Spain / Portugal

Georg Fischer S.A.
28046 Madrid
Phone +34 (0) 91 781 98 90
es.ps@georgfischer.com
www.gfps.com/es

Sweden

Georg Fischer AB
117 43 Stockholm
Phone +46 (0) 8 506 775 00
info.se.ps@georgfischer.com
www.gfps.com/se

Switzerland

Georg Fischer
Rohrleitungssysteme (Schweiz) AG
8201 Schaffhausen
Phone +41 (0) 52 631 30 26
ch.ps@georgfischer.com
www.gfps.com/ch

Taiwan

Georg Fischer Co., Ltd
San Chung Dist., New Taipei City
Phone +886 2 8512 2822
Fax +886 2 8512 2823
sgp.ps@georgfischer.com
www.gfps.com/tw

United Kingdom / Ireland

Georg Fischer Sales Limited
Coventry, CV2 2ST
Phone +44 (0) 2476 535 535
uk.ps@georgfischer.com
www.gfps.com/uk

USA / Caribbean

Georg Fischer LLC
9271 Jeronimo Road
Irvine, CA 92618
Phone +1 714 731 88 00
Fax +1 714 731 62 01
us.ps@georgfischer.com
www.gfps.com/us

International

Georg Fischer
Piping Systems (Switzerland) Ltd
8201 Schaffhausen/Schweiz
Phone +41 (0) 52 631 30 03
Fax +41 (0) 52 631 28 93
info.export@georgfischer.com
www.gfps.com/int

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

GF Piping Systems

Tel. (714) 731-8800, Toll Free (800) 854-4090, Fax (800) 426-7188

us.ps@georgfischer.com, www.gfpiping.com

