

# Moisture Generated During Construction

## About Polyiso Insulation

Polyiso is a rigid foam insulation used in more than 70% of commercial roof construction and offers a continuous insulation solution for commercial and residential wall assemblies. As one of North America's most widely used and readily available building products, Polyiso is a cost-effective insulation option for reducing building energy use and improving the overall service-life of roofs and walls.

The benefits of using Polyiso include:

- High R-value per inch of thickness
- Excellent fire test performance
- Extensive building code approvals
- Cost-effective continuous insulation (ci) solution
- Compatible with most roof and wall systems
- Dimensional stability
- Compressive strength
- Moisture resistance
- Thinner walls and roofs with shorter fasteners
- Long service life
- Preferred insurance ratings
- Virtually no global warming potential
- Zero ozone depletion potential
- Recyclable through reuse
- Recycled content (amount varies by product)
- Regional materials (nationwide production network)
- QualityMark<sup>CM</sup> certified LTRR-values

Polyiso roof insulation is used in built-up (BUR), modified bitumen, metal, ballasted single-ply, mechanically attached single-ply, and adhered single-ply roofing systems. These roofing systems depend on proper installation for successful performance. Although all roofing systems can be compromised by construction generated moisture, loose laid and mechanically attached systems are more likely to be affected because as the flexible membrane flutters, moisture laden air from the interior may be drawn in to the system.<sup>1</sup>

*Although not specifically a source of construction generated moisture, buildings under construction are susceptible to water/moisture intrusion from unfinished portions of the roof or adjacent components.*

In *The Manual of Low Slope Roof Systems* by Griffin & Fricklas. (pp.112), information regarding construction generated moisture is presented:

- A 4" thick concrete floor slab placed in an enclosed building generates 1 ton of water per 1000 square feet of concrete.
- The use of heaters, such as "salamanders," to provide more comfortable working conditions or to help dry the construction also generates large quantities of moisture. For each 200-pound tank of propane burned, 30 gallons of water are produced.
- Oil-burning heaters produce 1 gallon of water for every 1 gallon of oil burned.
- Paint, plaster and other water based construction materials may also contribute to moisture accumulation in the roofing system.

## Effects of moisture generated during construction on the roofing system:

- Condensed water vapor can collect in steel deck ribs causing corrosion and possible water intrusion into the building<sup>2</sup>.
- Condensed moisture can promote the growth of micro-organisms that can weaken or destroy building components and create health issues<sup>2</sup>.
- Liquid water entering the roof from rain or snow events can collect in the steel deck ribs and other levels of the system causing unseen damage.
- Moisture drawn into the roof system may affect the physical properties of roof insulation, including dimensional stability and thermal resistance.



Surround yourself with the best.

<sup>1</sup> Griffin & Fricklas. *The Manual of Low Slope Roof Systems*, pp.116  
<sup>2</sup> NRCA Roofing and Waterproofing Manual, 5th Edition, pp. 813

## Good construction practices to help minimize moisture problems:

- Provide adequate ventilation of enclosed construction areas to minimize the accumulation of construction generated moisture.
- Since most moisture is transported by air, sources of air movement should be identified and blocked.
- A decision to use a vapor retarder should only be made by the roof designer because the inclusion of a vapor retarder may affect insulation fastening requirements, wind uplift ratings, or other approvals.
- Multi-layered roof insulation applications help restrict air flow and moisture transport into the roof system.
- During application of the roofing system, the completed portion should be protected from liquid water entry at the end of each day. Prior to installation of insulation the deck should be allowed to dry.
- When installing a roof covering on a concrete deck, ensure that the deck is dry enough for application of prime coat, hot asphalt or cold adhesive, and subsequent roof materials.

### PIMA

For more than 30 years, PIMA (Polyisocyanurate Insulation Manufacturers Association) has served as the unified voice of the rigid polyiso industry proactively advocating for safe, cost-effective, sustainable and energy-efficient construction. PIMA's membership includes manufacturers of polyiso insulation and suppliers to the industry. The products of PIMA's members comprise the majority of the polyiso produced in North America.

PIMA produces technical bulletins to address frequently asked questions about polyiso insulation. These publications update and inform architects, specifiers, and contractors about and build consensus on the performance characteristics of polyiso insulation. Individual companies can provide specific information about their respective polyiso products.

For more information on polyisocyanurate insulation, visit [www.polyiso.org](http://www.polyiso.org)



[www.polyiso.org](http://www.polyiso.org) • [pima@pima.org](mailto:pima@pima.org)

1220 North Fillmore Street, Suite 400

Arlington, VA 22201

Phone: 703.258.0093

